


Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 43.3 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 150% - 1min

(5) Apparent output power

71.9 kVA

(6) Motor rated power output P_n

55 kW

(7) Rated output current

83 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

500 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 43.3 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 120% - 1min

(5) Apparent output power

93.5 kVA

(6) Motor rated power output P_n

75 kW

(7) Rated output current

108 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

500 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 50.5 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 150% - 1min

(5) Apparent output power

86.3 kVA

(6) Motor rated power output P_n

55 kW

(7) Rated output current

83 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

600 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 50.5 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 120% - 1min

(5) Apparent output power

112.2 kVA

(6) Motor rated power output P_n

75 kW

(7) Rated output current

108 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

600 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 58.2 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 150% - 1min

(5) Apparent output power

99.2 kVA

(6) Motor rated power output P_n

75 kW

(7) Rated output current

83 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

690 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses :



Standby losses : 58.2 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

461-0004, Japan

(4) Product's model identifier

VFAS3-6750PC

Series : TOSVERT VF-AS3
Nominal frequency : 50 Hz
Over load : 120% - 1min

(5) Apparent output power

129.1 kVA

(6) Motor rated power output P_n

90 kW

(7) Rated output current

108 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

690 VAC

(11) Exemption