
Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses: 6.3 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-2037PM

TOSVERT VF-S15 Series:

50 Hz Nominal frequency: 150% - 1min

Over load:

(5) Apparent output power

6.1 kVA

(6) Motor rated power output Pn

4 kW

(7) Rated output current

17.5 A

(8) Maximum operating temperature

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

200 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses :

6.5 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-2037PM

Series: TOSVERT VF-S15

Nominal frequency: 50 Hz

Over load: 150% - 1min

- (5) Apparent output power
- 7.3 kVA
- (6) Motor rated power output Pn
- 4 kW
- (7) Rated output current
- 17.5 A
- (8) Maximum operating temperature
- 50 °C
- (9) Rated supply frequency
- 50 Hz
- (10) Rated supply voltage
- 240 VAC
- (11) Exemption