
## Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses: 9.2 W

(2) Efficiency level

## IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-2110PM

Series: TOSVERT VF-S15

Nominal frequency: 50 Hz Over load: 150% - 1min

(5) Apparent output power

18.7 kVA

(6) Motor rated power output Pn

11 kW

(7) Rated output current

54 A

(8) Maximum operating temperature

50 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

200 VAC


(11) Exemption

## Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses:

(2) Efficiency level

## IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-2110PM

**TOSVERT VF-S15** Series:

50 Hz Nominal frequency: 150% - 1min

Over load:

(5) Apparent output power

22.4 kVA

(6) Motor rated power output Pn

11 kW

(7) Rated output current

(8) Maximum operating temperature

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

240 VAC

(11) Exemption