
Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses:

(2) Efficiency level

8.7 W

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-6022P

TOSVERT VF-S15 Series:

50 Hz Nominal frequency: 150% - 1min Over load:

(5) Apparent output power

3.5 kVA

(6) Motor rated power output Pn

2.2 kW

(7) Rated output current

(8) Maximum operating temperature

60 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

525 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses: 9.4 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-6022P

TOSVERT VF-S15 Series:

50 Hz Nominal frequency: 150% - 1min

Over load:

(5) Apparent output power

4.1 kVA

(6) Motor rated power output Pn

2.2 kW

(7) Rated output current

(8) Maximum operating temperature

60 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

600 VAC

(11) Exemption