
Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses: 11.5 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-6150P

Series: TOSVERT VF-S15

Nominal frequency: 50 Hz Over load: 150% - 1min

(5) Apparent output power

20 kVA

(6) Motor rated power output Pn

15 kW

(7) Rated output current

22 A

(8) Maximum operating temperature

60 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

525 VAC


(11) Exemption

Ecodesign requirements for variable speed drives

Technical documentation for the purposes of conformity assessment pursuant to Directive 2009/125/EC

(1) Losses

Power losses:



Standby losses: 13.1 W

(2) Efficiency level

IE2

(3) Manufacturer's name or trade mark, commercial registration number and address

Toshiba Schneider Inverter Corporation

MAZAK ART PLAZA 13F, 1-19-30, Aoi, Higashi Ward, Nagoya City, Aichi Prefecture,

460-0004, Japan

(4) Product's model identifier

VFS15-6150P

Series: TOSVERT VF-S15

Nominal frequency: 50 Hz
Over load: 150% - 1min

(5) Apparent output power

22.9 kVA

(6) Motor rated power output Pn

15 kW

(7) Rated output current

22 A

(8) Maximum operating temperature

60 °C

(9) Rated supply frequency

50 Hz

(10) Rated supply voltage

600 VAC

(11) Exemption